

STAINLESS STEEL APPLIANCE CONNECTORS

Suitable for indoor and outdoor installations including:

- Appliances
- Water heaters
- Grills
- Fire pits
- Fireplaces



10-3131-12

RMI Part No.	Description
90-1022	3/8" OD X 3/8" FIP
90-1031	3/8" OD X 1/2" MIP
90-1031-A	3/8" OD X 1/2" MIP BLACK
90-1032	3/8" OD X 1/2" FIP
90-2021-A	1/2" OD X 3/8" MIP BLACK
90-2022	1/2" X 3/8" FIP
90-2031	1/2" OD X 1/2" MIP
90-2031-A	1/2" OD X 1/2" MIP BLACK
90-2032	1/2" OD X 1/2" FIP
90-2042	1/2" OD X 3/4" FIP
90-3031	5/8" OD X 1/2" MIP
90-3032	5/8" OD X 1/2" FIP
90-3041	5/8" OD X 3/4" MIP
90-3042	5/8" OD X 3/4" FIP
90-4041	1" OD X 3/4" MIP
90-4042	1" OD X 3/4" FIP
90-5052	1-1/4" OD X 1" FIP

10 SERIES - 3/8" OD (1/4" ID)

RMI Part No. 1/2" MIP 1/2" MIP	Box Qty	RMI Part No. 1/2" MIP 1/2" FIP	Box Qty	Length	BTU Capacity (LP)
10-3131-12	25	10-3132-12	25	12"	76,800
10-3131-18	25	10-3132-18	25	18"	70,080
10-3131-24	25	10-3132-24	25	24"	64,000
10-3131-30	25	10-3132-30	25	30"	58,240
10-3131-36	25	10-3132-36	25	36"	53,440
10-3131-48	25	10-3132-48	25	48"	45,280
10-3131-60	12	10-3132-60	12	60"	39,840
10-3131-72	12	10-3132-72	12	72"	36,960

20 SERIES - 1/2" OD (3/8" ID)

RMI Part No. 1/2" MIP 1/2" MIP	Box Qty	RMI Part No. 1/2" MIP 1/2" FIP	Box Qty	Length	BTU Capacity (LP)
20-3131-12	25	20-3132-12	25	12"	163,200
20-3131-18	25	20-3132-18	25	18"	148,960
20-3131-24	25	20-3132-24	25	24"	136,000
20-3131-30	25	20-3132-30	25	30"	123,360
20-3131-36	25	20-3132-36	25	36"	113,760
20-3131-48	25	20-3132-48	25	48"	96,800
20-3131-60	12	20-3132-60	12	60"	85,120
20-3131-72	12	20-3132-72	12	72"	78,560

30 SERIES - 5/8" OD (1/2" ID)

RMI Part No. 1/2" MIP 1/2" MIP	Box Qty	RMI Part No. 1/2" MIP 1/2" FIP	Box Qty	Length	BTU Capacity (LP)
30-3131-12	25	30-3132-12	25	12"	288,000
30-3131-18	25	30-3132-18	25	18"	262,720
30-3131-24	25	30-3132-24	25	24"	240,000
30-3131-30	25	30-3132-30	25	30"	217,600
30-3131-36	25	30-3132-36	25	36"	200,000
30-3131-48	25	30-3132-48	25	48"	169,600
30-3131-60	12	30-3132-60	12	60"	149,120
30-3131-72	12	30-3132-72	12	72"	137,600



Non-stock/special order items are not cancellable or returnable

Shop online at www.raymurray.com or call **800-628-5044**

BLACK EPOXY COATED STAINLESS STEEL GAS CONNECTORS

For gas logs and gas fireplace inserts

- Designed to reduce glare and hide the connector from view
- High-temp coating withstands temperatures up to 350°F
- Adaptors and flare nuts are plated with zinc di-chromate to reduce visibility



20A-2131-12

10A SERIES - BLACK 3/8" OD CONNECTORS

RMI Part No. 3/8" MIP x 1/2" MIP	Box Qty	Length	BTU Capacity (LP)
10A-2131-12	25	12"	76,800
10A-2131-18	25	18"	70,080
10A-2131-24	25	24"	64,000
10A-2131-36	25	36"	57,700

20A SERIES - BLACK 1/2" OD CONNECTORS

RMI Part No. 3/8" MIP x 1/2" MIP	Box Qty	RMI Part No. 3/8" MIP x 1/2" FIP	Box Qty	Length	BTU Capacity (LP)
20A-2131-12	25	20A-2132-12	25	12"	163,200
20A-2131-18	25	20A-2132-18	25	18"	148,960
20A-2131-24	25	20A-2132-24	25	24"	136,000
20A-2131-36	25	20A-2132-36	25	36"	113,760

WHISTLE-FREE PREMIUM BLACK COATED APPLIANCE CONNECTORS

- Coated with high-temp black epoxy for reduced visibility
- Special corrugation design eliminates whistling produced by high-BTU gas appliances



T102-2131-12

T102 SERIES - BLACK WHISTLE-FREE 3/8" OD CONNECTORS

RMI Part No. 3/8" MIP 1/2" MIP	Box Qty	Length	BTU Capacity (LP)
T102-2131-12	25	12"	76,800
T102-2131-18	25	18"	70,080
T102-2131-24	25	24"	64,000
T102-2131-36	25	36"	57,700

T202 SERIES - BLACK WHISTLE-FREE 1/2" OD CONNECTORS

RMI Part No. 3/8" MIP 1/2" MIP	Box Qty	Length	BTU Capacity (LP)
T202-2131-12	25	12"	163,200
T202-2131-18	25	18"	148,960
T202-2131-24	25	24"	136,000
T202-2131-36	25	36"	113,760

HIGH BTU PVC COATED APPLIANCE CONNECTORS

- Flame-resistant antimicrobial coating provides UV and corrosion protection
- Ideal for outdoor installations
- For commercial HVAC units, water heaters, boilers, furnaces, etc.



41-4142-24

41 SERIES - PVC COATED HIGH FLOW 1" OD CONNECTORS

RMI Part No. 3/4" MIP x 3/4" FIP	Length	BTU Capacity (LP)
41-4142-24	24"	465,440
41-4142-36	36"	409,440
41-4142-48	48"	344,000

51 SERIES - PVC COATED HIGH FLOW 1-1/4" OD CONNECTORS

RMI Part No. 3/4" MIP x 3/4" FIP	Length	BTU Capacity (LP)
51-5152-24	24"	930,880
51-5152-36	36"	825,440
51-5152-48	48"	708,320



COMMERCIAL MOVEABLE APPLIANCE CONNECTORS

- Stainless steel corrugated tube with stainless braid reinforcement
- Durable antimicrobial coating for added protection and easy cleaning
- Adjustable restraining devices to protect connector when appliance is moved

Thread Size	Length	RMI Part No.	RMI Part No.	BTU Capacity (LP)
		No Quick Disconnect	Quick Disconnect	
1/2" FNPT	36"	1650BP-36	1650BPQ-3	77,000
1/2" FNPT	48"	1650BP-48	1650BPQ-4	68,000
1/2" FNPT	60"	1650BP-60	1650BPQ-5	60,000
1/2" FNPT	72"	1650BP-72	1650BPQ-6	55,000
3/4" FNPT	36"	1675BP-3	1675BPQ-3	218,000
3/4" FNPT	48"	1675BP-4	1675BPQ-4	180,000
3/4" FNPT	60"	1675BP-5	1675BPQ-5	158,000
3/4" FNPT	72"	1675BP-6	1675BPQ-6	139,000

* 1" and 1-1/4" connectors also available - please contact customer service for more info



COMMERCIAL APPLIANCE CONNECTOR

RESTRAINING DEVICES

RMI Part No.	Description
RDC-36	36" Restraining Device
RDC-48	48" Restraining Device
RDC-60	60" Restraining Device

THERMAL QUICK CONNECT COUPLINGS

RMI Part No.	Description
A50	QD Coupling for 1/2" Connectors
A75-M/F	QD Coupling for 3/4" Connectors



RESTRAINING KIT



APPLIANCE CONNECTOR INSTALLED



Non-stock/special order items are not cancellable or returnable

Shop online at www.raymurray.com or call 800-628-5044