

Thermoid Bobtail Hose



BOBTAIL DELIVERY HOSE WITH FACTORY CRIMPED PRO-SUR BRASS ENDS

RMI Part No.	I.D.	O.D.	Length	Shipping Weight
TLPGH-1-100CT*	1"	1.5"	100'	63 Lbs
TLPGH-1-125CT	1"	1.5"	125'	77 Lbs
TLPGH-1-150CT	1"	1.5"	150'	92 Lbs
TLPGH-1-175CT	1"	1.5"	175'	102 Lbs

* available as a special order

POLAR FLEX LOW TEMP (-55F) DELIVERY HOSE WITH FACTORY PRESSURE TESTED ENDS

- UL-21 approved
- 350 Max WP 1750 min Burst
- Smooth cover, Thermalon
- Oil Resistant and Flame retardant
- -55 to 180 Deg. F
- Four-spiral reinforcement
- Tested to D.O.T. Requirements



THERMOID POLARFLEX

POLAR FLEX HOSE

RMI Part No.	I.D.	O.D.	Length	Shipping Weight
TLPGH-1-125CTPF	1"	1.5"	125'	77
TLPGH-1-150CTPF	1"	1.5"	150'	92

FAIRVIEW BOBTAIL DELIVERY HOSE

RMI Part No.	I.D.	O.D.	Length	Min Temp	Max Temp
I16C1500MP16MPI6-P1	1"	1.5"	125'	-60°F	212°F
I16C1800MP16MPI6-P1	1"	1.5"	150'	-60°F	212°F

Parker Bobtail Hose



BOBTAIL DELIVERY HOSE WITH FACTORY CRIMPED PRESSURE TESTED BRASS ENDS

- UL-21 approved
- 350 Max WP 1750 min Burst
- Smooth cover, Thermalon
- Oil Resistant and Flame retardant
- -40 to 180 Deg. F
- Four-spiral reinforcement
- Tested to D.O.T. Requirements



PARKER BOBTAIL HOSE

RMI Part No.	I.D.	O.D.	Length	Shipping Weight
LPGH-1-125CT	1"	1.5"	125'	80
LPGH-1-150CT	1"	1.5"	150'	95
LPGH-3/4-125CT	3/4"	1.25"	125'	70
LPGH-3/4-150CT	3/4"	1.25"	150'	83

PARKER X-TREME LOW-TEMP BOBTAIL HOSE

- -65 to 180 degrees F
- Neoprene Cover



PARKER X-TREME HOSE

RMI Part No.	I.D.	O.D.	Length	Shipping Weight
EXLPGH-1-125CT	1"	1.5"	125'	80
EXLPGH-1-150CT	1"	1.5"	150'	95

Smart-Hose Passive Shutdown System DOT & Facility Hose

SMART-HOSE PASSIVE SHUTDOWN SYSTEM -DOT & FACILITY HOSE

The Smart-Hose meets the requirements of the DOT standards and additions to NFPA for a passive shut down system. The patented system features an internal cable connected to normally unseated "valve plungers or wedges" located on each end of the cable. In the event of coupling -to-hose separation, stretching to the point of an unsafe condition or hose severance, the valve "wedges" are released and instantly seat, stopping the flow in both directions.

- Complies with HM-225
- Provides advanced safety
- Prevents product loss
- Prevents property damage
- No Added field maintenance beyond normal hose care and inspections
- Factory Recoupling program available

LIFELINE BREAK-AWAY FEATURES

- Available for 2" DOT or Facility Hose
- Engineered break away point
- Factory rebuildable

1 INCH SMART-HOSE ASSEMBLIES

RMI Part No.	Description
CG-LPG-16-R10	1" x 10' Smart-Hose
CG-LPG-16-R15	1" x 18.5' Smart-Hose
CG-LPG-16-R20	1" x 20' Smart-Hose
CG-LPG-16-R25	1" x 25' Smart-Hose
CG-LPG-16-R30	1" x 30' Smart-Hose

2 INCH SMART-HOSE ASSEMBLIES WITH BREAKAWAY

RMI Part No.	Description
CG-LPG-32-BR15-3	2" x 15' Smart hose with breakaway
CG-LPG-32-BR20-3	2" x 18.5' Smart hose with breakaway

2 INCH FACILITY HOSE WITH BREAKAWAY

RMI Part No.	Description
CG-LPG-32-BR12-3F	2" x 12' Smart-Hose with breakaway
CG-LPG-32-BR15-3F	2" x 15' Smart-Hose with breakaway



NORMAL FLOW - VALVE OPEN



HOSE BREAK - VALVE CLOSED

1.25 INCH SMART-HOSE ASSEMBLIES

RMI Part No.	Description
CG-LPG-20-R10	1.25" x 10' Smart-Hose
CG-LPG-20-R15	1.25" x 18.5' Smart-Hose
CG-LPG-20-R20	1.25" x 20' Smart-Hose
CG-LPG-20-R25	1.25" x 25' Smart-Hose
CG-LPG-20-R30	1.25" x 30' Smart-Hose

2 INCH SMART-HOSE ASSEMBLIES

RMI Part No.	Description
CG-LPG-32-R10-3	2" x 10' Lifeline 3
CG-LPG-32-R15-3	2" x 15' Lifeline 3
CG-LPG-32-R20-3	2" x 18.5' Lifeline 3
CG-LPG-32-R25-3	2" x 25' Lifeline 3
CG-LPG-32-R30-3	2" x 30' Lifeline 3

2 INCH SMART-HOSE FACILITY HOSE

RMI Part No.	Description
CG-LPG-32-R10-3F	2" x 10' Facility Hose
CG-LPG-32-R15-3F	2" x 15' Facility Hose



Non-stock/special order items are not cancellable or returnable

Shop online at www.raymurray.com or call 800-628-5044

Propane Hose, Fittings, and Wraps



TECH TIPS:

- Hose manufacturers do not recommend the use of screw-in type reusable couplings
- The cover of all LP-gas Hose must be perforated to prevent gas buildup among the various layers of the hose
- LP gas hose can be used for natural gas service in outdoor applications only, and at a maximum pressure of 50 psi.

DAYCO/PARKER BRAND HOSE

- UL-21 approved
- 350 Max WP 1750 min Burst
- Smooth cover, Thermalon
- Abrasive Resistant
- -40 to 180 Deg. F

RMI Part No.	I.D.	O.D.	Weight (lbs) per 100'	Reel Length
LPGH-1/4	1/4"	0.610"	14	750'
LPGH-3/8	3/8"	3/4"	22	600'
LPGH-1/2	1/2"	0.937"	30	500'
LPGH-3/4	3/4"	1-1/4"	53	350'
LPGH-1	1"	1-1/2"	66	300'

Note: Bulk Hose reel lengths may not be continuous and may be sectioned in up to 3 varying lengths.

ACCUFLEX THERMOPLASTIC HOSE

RMI Part No.	I.D.	O.D.	Weight (lbs) per 100'	Reel Length
LPGH-5/16	5/16"	.580"	16	600'

DAYCO BULK TRANSFER HOSE

- UL-21 approved
- 350 Max WP 1750 min Burst
- Wrapped Impression Neoprene cover
- 3 braid reinforcement

RMI Part No.	I.D.	O.D.	Weight (lbs) per 100'
LPGH-1-1/4	1.25"	1.875"	95
LPGH-1-1/2	1.50"	1.78125"	125
LPGH-2	2"	2.75"	170

PROWRAP HOSE PROTECTION

- Easy to install
- Tight grip prevents sliding
- UV Resistant
- -70 to 180 Deg. F



RMI Part No.	Description
PWLD-16	66ft length 1/4" -3/4" hose
PWLD-20	66ft Length 1"-1-1/4" hose
PWLD-32	12.5 Ft. length 1-1/2" - 2" Hose

RAY MURRAY INC. CRIMPED HOSE ASSEMBLY

RMI Factory Trained personnel will make custom crimped hose assemblies to your requirements.

If you require a hose assembly to be tested to DOT requirements they can be made up to the sizes below.

(Note: Custom wire braid flex connectors can be made as well)



RMI Part No.	Hose I.D.	Thread Size	Minimum Length	Crimp Fitting Part No.
1/4 HOSEKIT	1/4"	1/4"	6"	4NP-4SB
3/8 HOSEKIT	3/8"	3/8"	6"	6NP-6SB
1/2 HOSEKIT	1/2"	1/2"	6-3/4"	8NP-8SB
3/4 HOSEKIT	3/4"	3/4"	6-3/4"	12NP-12SC
1 HOSEKIT	1"	1"	7"	16MP-16LAR
1 1/4 HOSEKIT	1-1/4"	1-1/4"	9"	20NP-20SBA
1 1/2 HOSEKIT	1-1/2"	1-1/2"	9-1/2"	24NP-24BC
2 HOSEKIT	2"	2"	11-1/4"	32NP-32LA

RAY MURRAY TESTED CRIMPED HOSE ASSEMBLIES

RMI Part No.	Hose I.D.	Thread Size	Minimum Length	Max Length
3/4 HOSEKIT-TESTED	3/4"	3/4"	6-3/4"	50ft
1 HOSEKIT-TESTED	1"	1"	7"	50ft
1 1/4 HOSEKIT-TESTED	1-1/4"	1-1/4"	9"	40ft
1 1/2 HOSEKIT-TESTED	1-1/2"	1-1/2"	9-1/2"	30ft
2 HOSEKIT-TESTED	2"	2"	11-1/4"	30ft



Non-stock/special order items are not cancellable or returnable

Shop online at www.raymurray.com or call **800-628-5044**

Motor Fuel Hose & Couplings

PIPE TO HOSE SWIVEL ADAPTORS

RMI Part No.		NPT pipe	NPS swivel
Male Adaptor	Female Adaptor		
107-8-8	207-8-8	1/2"	1/2"
107-12-12	207-12-12	3/4"	3/4"
107-16-16	207-16-16	1"	1"
107-20-20	207-20-20	1-1/4"	1-1/4"
107-24-24	207-24-24	1-1/2"	1-1/2"
107-32-32	207-32-32	2"	2"



LPG STAINLESS STEEL BRAID HOSE WITH CLOTH

Seamless oil-resistant synthetic rubber high temperature hose. One Stainless steel wire braid and two polyester braids. Cloth cover is impregnated with fire and mildew-resistant compounds. Typically seen on forklifts and industrial trucks.



PARKER STAINLESS STEEL BRAID HOSE

RMI Part No.	I.D.	Hose O.D.	Working pressure	Burst Pressure
SS25UL-4	3/16"	0.52	350	1750
SS25UL-5	1/4"	0.58	350	1750
SS25UL-6	5/16"	0.67	350	1750
SS25UL-8	13/32"	0.77	350	1750
SS25UL-10	1/2"	0.92	350	1750
SS25UL-12	5/8"	1.08	350	1750

BRASS BULKHEAD FITTINGS


RMI Part No.	Description
BH-38	3/8" Flare straight through
BHT-38	3/8" Flare x 1/4" NPT x 1/4" NPT Tee
MET444	1/4" Flare x 1/4" NPT x 1/4" NPT Tee



DRIFT HOSE

A drift hose can be used to transfer liquid propane from a forklift cylinder to an empty container by pressure differential. Fittings can be removed from the drift hose to convert from forklift adapter to POL.

RMI Part No.	Description
DRIFTHOSE	1/2" x 10' Drift Hose Kit



FEMALE ANGLE FF FOR SS BRAID HOSE

RMI Part No.	Hose I.D.	Female Flare size	Angle
27720-6	5/16"	3/8"	45 degree
27920-6	5/16"	3/8"	90 Degree



TWO-BOLT CLAMP TYPE HOSE COUPLING

RMI Part No.		Hose I.D.	Thread size
Marshall Excelsior	Fisher		
ME3162-08	M3162-08	1/2"	1/2"
ME3162-12	M3162-12	3/4"	3/4"
ME3162-16	M3162-16	1"	1"
ME3162-20	M3162-20	1-1/4"	1-1/4"
ME3162-24	M3162-24	1-1/2"	1-1/2"
ME3162-32	M3162-32	2"	2"
-	M3162-48	3"	3"



HOSE ENDS FOR SS HOSE

FEMALE 45D FLARE

RMI Part No.	Hose I.D.	Female 45 Flare
20820-4	3/16"	1/4"
20820-5	1/4"	1/4"
20820-6	5/16"	1/4"
20820-8	13/32"	1/2"
20820-8-10	1/2"	1/2"
20820-10	1/2"	5/8"
20820-12-12	5/8"	3/4"



MALE NPT

RMI Part No.	Hose I.D.	Male NPT
20120-4-4	3/16"	1/4"
20120-4-5	1/4"	1/4"
20120-4-6	5/16"	1/4"
20120-8-8	13/32"	1/2"
20120-8-10	1/2"	1/2"
20120-12-10	1/2"	3/4"
20120-12-12	5/8"	3/4"

