

### HIGH COLLAR DOT CYLINDERS

Excellent for both stationary and portable cylinder installations. Lightweight & rugged for either domestic or construction applications.

RMI Part No.	Propane Capacity (lbs)	Valve Type	Diameter	Height	Tare Weight (lbs)
50HC-10	50	POL 10%	14.5"	28.5"	46
60HC-10	60	POL 10%	12.2"	43.5"	46
100HC-10	100	POL 10%	15.1"	46.5"	71
100HC-M	100	Multivalve	15.1"	46.5"	71



100HC-10

### UNIVERSAL LIFT TRUCK CYLINDERS

Standard valves include liquid service valve, relief valve, universal float gauge, 10% valve. Universal lift truck cylinders can be used in vertical or horizontal service. Cylinders include 1428M ACME connector installed. Steel or Aluminum cylinders are available.

Aluminum		Steel		Propane Capacity (lbs)	Diameter (in)	Height (in)
Part No.	Weight (lbs)	Part No.	Weight (lbs)			
AL20MF-F-A	19	20MF-F-A	25.5	20	12.25	20-1/8
AL33MF-F-A	23.5	33MF-F-A	35	33.5	12.25	27-5/8
AL43MF-F-A	26.5	43MF-F-A	41	43.5	12.25	33-5/8



33MF-F-A



AL33MF-F-A

### PORTABLE STEEL CYLINDERS

Meet or exceed specifications 4BA-240 or 4BW-240. Durable white powder coated finished cylinder is excellent for grills, RV, and torch applications.

RMI Part No.	Propane Capacity (lbs)	Diameter (in)	Height (in)	Weight (lbs)
5-TYPE1-OPD	5	8	12	10
10-TYPE1-OPD	10	8.9	17.4	15
11-TYPE1-OPD	11	12.2	12.4	14
20-TYPE1-OPD	20	12.2	17.6	18
30-TYPE1-OPD	30	12.2	23.4	26
40-TYPE1-OPD	40	12.2	29.4	31



20-TYPE1-OPD

### PORTABLE ALUMINUM CYLINDERS

These meet or exceed DOT specifications 4E-240. Clear aluminum finish cylinders are used on many torch, RV, and grill applications.

"RMI Part No."	Propane Capacity (lbs)	Diameter (in)	Height (in)	Weight (lbs)
AL20-OPD	20	12-1/2	20-5/8	12
AL30-OPD	30	12-1/2	26-1/2	17
AL40-OPD	40	12-1/2	32	19



ALUMINUM CYLINDERS