



## **REZNOR**



#### **REZNOR UBZ SEPARATED COMBUSTION HEATERS**

Made in U.S.A. Model UBZ gas-fired, separated combustion, high-static blower fan, 82 - 83% thermal efficiency, commercial/industrial unit heaters are great for space heating applications. These models use outside air for combustion to prevent dirt, lint, dust or other contaminants in the indoor atmosphere from being burned. Each size cabinet is easily suspended from four suspension points. The low voltage terminal strip on the outside of the cabinet makes connecting control wiring easy with no panels to remove. The addition of terminal G to the strip, along with the new design of the circuit board, allows for fan only operation (without adding relays). Integrated circuit board with 7 segment display, external status indicating LED, Toore titanium stabilized aluminized steel heat exchanger, Patented single burner combustion system including a one-piece burner assembly, vibration/noise isolated fan and venter motor - designed for low noise operation.



UBZ

Model #	Gas Type	Operation	Btu's	Description	Length	Depth	Height
UBZ30	LP	Direct Spark Ignition	30,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	27"	40-3/32"	13-3/4"
UBZ45	LP	Direct Spark Ignition	45,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	27"	40-3/32"	13-3/4"
UBZ60	LP	Direct Spark Ignition	60,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	27"	40-3/32"	16-3/4"
UBZ75	LP	Direct Spark Ignition	75,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	27"	40-3/32"	16-3/4"
UBZ100	LP	Direct Spark Ignition	100,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	27"	48-1/8"	24-3/4"
UBZ125	LP	Direct Spark Ignition	125,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	27"	47-5/8"	24-3/4"
UBZ150	LP	Direct Spark Ignition	150,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	38-3/16"	64-3/4	20-1/8"
UBZ175	LP	Direct Spark Ignition	175,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	38-3/16"	64-3/4	20-1/8"
UBZ200	LP	Direct Spark Ignition	200,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	38-3/16"	64-3/4	20-1/8"
UBZ225	LP	Direct Spark Ignition	225,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	38-3/16"	68-1/8"	26-1/8"
UBZ250	LP	Direct Spark Ignition	250,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	38-3/16"	68-1/8"	26-1/8"
UBZ300	LP	Direct Spark Ignition	300,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	41"	68-1/8"	34-1/8"
UBZ350	LP	Direct Spark Ignition	350,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	41"	68-1/8"	34-1/8"
UBZ400	LP	Direct Spark Ignition	400,000	Separated Combustion,Alum Heat Exchanger,Blower,Commercial/Industrial Heater	41"	68-1/8"	34-1/8"

<sup>\*\*\*</sup> Also available for Natural Gas - add "N" before the Model #



293



#### **Reznor Heaters**

# **REZNOR**



### **REZNOR UDX UNIT HEATERS**

Made in U.S.A. Model UDX gas-fired unit heaters are great for space heating applications. These units are power vented to eliminate heat losses up the flue pipe. Each size cabinet is easily suspended from either two or four suspension points. Or, an optional hanger kit for Sizes 30-125 allows for ceiling mounting. The low voltage terminal strip on the outside of the cabinet makes connecting control wiring easy with no panels to remove. The addition of terminal G to the strip, along with the new design of the circuit board, allows for fan only operation (without adding relays). Integrated circuit board with 7 segment display, external status indicating LED, Toore titanium stabilized aluminized steel heat exchanger, Patented single burner combustion system including a one-piece burner assembly, vibration/noise isolated fan and venter motor - designed for low noise operation.



UDX

Model #	Gas Type	Operation	Btu's	Description	Length	Depth	Height
UDX30	LP	Direct Spark Ignition	30,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	27"	29-3/4"	13-3/4"
UDX45	LP	Direct Spark Ignition	45,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	27"	29-3/4"	13-3/4"
UDX60	LP	Direct Spark Ignition	60,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	27"	27"	16-3/4"
UDX75	LP	Direct Spark Ignition	75,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	27"	27-5/8"	16-3/4"
UDX100	LP	Direct Spark Ignition	100,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	27"	34-9/32"	24-3/4"
UDX125	LP	Direct Spark Ignition	125,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	27"	34-9/32"	24-3/4"
UDX150	LP	Direct Spark Ignition	150,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	38-3/16"	48-7/16"	20-1/8"
UDX175	LP	Direct Spark Ignition	175,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	38-3/16"	48-7/16"	20-1/8"
UDX200	LP	Direct Spark Ignition	200,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	38-3/16"	48-7/16"	20-1/8"
UDX225	LP	Direct Spark Ignition	225,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	38-3/16"	48-7/16"	26-1/8"
UDX250	LP	Direct Spark Ignition	250,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	38-3/16"	48-7/16"	26-1/8"
UDX300	LP	Direct Spark Ignition	300,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	41"	48-29/32"	34-1/8"
UDX350	LP	Direct Spark Ignition	350,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	41"	48-29/32"	34-1/8"
UDX400	LP	Direct Spark Ignition	400,000	Power Vented,Alum Heat Exchanger,Commerical/Industrial Heater	41"	48-29/32"	34-1/8"

<sup>\*\*\*</sup> Also available for Natural Gas - add "N" before the Model #