

Aluminum Cylinders

ALUMINUM CYLINDERS FOR CO₂

- Specifications: DOT-3AL & TC-3ALM designed.
- Alloy: Manufactured from high strength aluminum alloy 6061-T6
- Markings: As required by specification. Additional markings available upon request
- Accessories: Valves installed upon request.
 - Other sizes available upon request

PART #	SERVICE PRESSURE (PSI)	CO ₂ capacity (Lbs)	DIAMETER IN	LENGTH In	Empty WEIGHT Lbs	Thread Size
C2.5V	1800	2.5	4.4	10.4	3.6	.750-16UNF-2B
C5V	1800	5	5.3	9	6.2	1.125-12UNF-2B
C10V	1800	10	6.9	16.6	12.9	1.125-12UNF-2B
C20V	1800	20	8	23.3	23	1.125-12UNF-2B
C35V	1800	35	8	38	34.8	1.125-12UNF-2B
C50V	1800	50	8.6	46.5	50.6	1.125-12UNF-2B

ALUMINUM CYLINDERS FOR INDUSTRIAL USES

- Specifications: DOT-3AL & TC-3ALM designed.
- Alloy: Manufactured from high strength aluminum alloy 6061-T6
- Markings: As required by specification. Additional markings available upon request
- Accessories: Valves installed upon request.
 - Other sizes available upon request

PART #	SERVICE PRESSURE (PSI)	DIAMETER IN	LENGTH In	Empty WEIGHT Lbs	OXYGEN cu ft	Thread Size
14	2216	3.2	9	1.8	4	A
16	2216	3.2	11.8	2.2	5.8	A
122	2216	5.3	17.1	8.6	22.9	B
160	2216	7.3	23.5	22.6	60.9	B
188	2216	7.3	32.9	30.3	89.9	B
1122	2216	8	36.3	39.5	121.9	B
1150	2015	8	47.9	48.5	153.2	B
1265	2216	9.8	52.8	85.3	265.1	B

A = .750-16UNF-2B

B = .750-16UNF-28B or 1.125-12UNF-2B



ALUMINUM INDUSTRIAL



Aluminum Cylinders

ALUMINUM CYLINDERS FOR MEDICAL USES

- Specifications: DOT-3AL & TC-3ALM designed
- Alloy: Manufactured from high strength aluminum alloy 6061-T6
- Markings: As required by specification. Additional markings available upon request
- Finish: Standard finish is brushed body with green crown (white crown for Canada) and clear paint
- Accessories: Valves installed upon request. M60 and larger are available with either a carrying handle or protective caps and collars.
 - Other sizes available upon request

RMI Part No.	Service Pressure psi	Diameter in	Length in	Cylinder Weight lbs	Oxygen cu ft	Thread Size
M2	2216	2.5	5.9	0.7	1.6	.750-16UNF-2B
M4	2216	3.19	8.4	1.6	3.7	.750-16UNF-2B
M6	2216	3.19	11.8	2.3	5.7	.750-16UNF-2B
ML6	2015	4.38	7.6	2.8	5.8	.750-16UNF-2B
M9	2015	4.38	10.8	3.6	8.6	.750-16UNF-2B
MD	2015	4.38	16.2	5.1	14.3	.750-16UNF-2B
ME	2015	4.38	25.6	7.5	23.9	.750-16UNF-2B
M22	2216	5.25	16.5	8.2	8.3	.750-16UNF-2B
M60	2216	7.25	22.9	21.9	60	1.125-12UNF-2B
M90	2216	7.25	32.6	29.8	90	1.125-12UNF-2B
M122	2216	8	36.3	39.5	121.9	1.125-12UNF-2B
M150	2015	8	47.9	48.5	153.2	1.125-12UNF-2B
M265	2216	9.8	51.4	85.3	265.1	1.125-12UNF-2B



MEDICAL CYL COLOR

***Valve shown is not included with the cylinder.**