

Leak Detectors & Sealants

GASKIT® ECO

GASKIT® ECO Leak Detector is Non-Toxic and 100% Biodegradable leak detection liquid specifically formulated for commercial and industrial use to locate leaks wherever compressed gases are used.

GASKIT® ECO Leak Detector is compatible with stainless steel, Steel, cast iron, ductile iron, copper, nylon, rubber, MDPE, HDPE, and others!

- Oxygen safe in accordance with Mil. Spec MIL-L-25567
- Protects against static electricity
- Longer adhesion fluid stays on surfaces longer, vertical and horizontal pipes

RMI Part No.	Description	Case Qty	Color
GASKIT-LT-ECO	LoTemp (10°)-1 Gallon	4 Gallons	Green
GASKIT-XL -ECO	Extra Lo Temp (-40°)-1 Gallon	4 Gallons	Med. Blue
GASKIT-LT-ECO-55	LoTemp (10°)- 55 Gallon Drum	55 Gal Drum	Green
GASKIT-XL -ECO-55	Extra Lo Temp (-40°)- 55 Gallon Drum	55 Gal Drum	Med. Blue



ECO GASKIT-LT

BRUSH, SQUEEZE & SPRAY BOTTLE

- Wide neck bottle and brush for easy application
- Pint bottle with spray nozzle
- Handy squeeze bottle

RMI Part No.	Description
LD-BOTTLE	Empty Pint Bottle & Brush
LD-SPRAY	Empty Pint Bottle W/Sprayer
LD-DAUBER	Empty 8oz. Bottle & Dauber
WP-120	Empty 80oz. Squeeze Bottle



LD-BOTTLE



LD-SPRAY

LEAK DETECTOR SOLUTION

GAS-KIT® 5-second Leak detector solution is fast and dependable, and finds even the smallest leaks. Available in regular or low temperature for sub-freezing temperatures. Available in 55 gallon Drums drop shipped from factory.

RMI Part No.	Description	Case Qty	Color
GASKIT-REG	Regular (27 Deg F)- 1 Gallon	4 Gallons	Green
GASKIT-LT	Lo Temp(-10 Deg F)-1 Gallon	4 Gallons	Red
GASKIT-XL	Extra Low Temp (-50 Deg F)- 1 Gallon	4 Gallons	Pink
GASKIT-CG	For O2 (27 Deg F)- 1 Gallon	4 Gallons	Blue
GasKit-Type II	Low Temp O2 (-65 deg F)- 1Gallon	4 Gallons	Lt. Blue



GASKIT-LT

THREAD SEALANTS

OC-3

Use oxygen compatible OC3 to seal threaded connections on cylinder valves more effectively than Teflon tape.

OC-5 and OC-7

Can be used in High Vacuum 10⁻⁷ Torr applications where exposure to corrosive gases is probable.

They are superior lubricants which provide leak tight sealing in a wide range of vacuum requirements.

These off-white homogenous grease and paste formulations provide unique sealing and lubricating solutions, as their properties remain unaltered over a wide temperature ranges, from cryogenic through thermally stable to +450°F. Both are non-flammable, non-migrating, non-toxic, odorless, and waterproof as well as anti-corrosive, anti-galling, anti-seize, and dielectric and lubricating.

Not recommended for aluminum against aluminum applications. Do not use with concentrated alkalis, fluorine(liquid) or chlorine trifluoride(liquid).

All OC products are approved by the major industrial gas providers.

RMI Part No.	Description
OC-3	Oxygen Safe Thread Sealant Paste 4oz Tube
OC3-16	Oxygen Safe Thread Sealant Paste 16oz Jar
OC-5	Oxygen Safe Thread Paste 2oz Jar
OC-5-16	Oxygen Safe Thread Paste 16oz Jar
OC-7	Oxygen Safe Grease 2oz Jar
OC-7-16	Oxygen Safe Grease 16oz Jar
O2TT-1/2	Green, Oxygen Safe, High Density, Teflon Tape 1/2" x 520" Roll
TT41	White High Density, Teflon Tape 1/2" x 520" Roll
TT41Y	Yellow High Density, Teflon Tape 1/2" x 520" Roll
O2TT-3/4	Green, Oxygen Safe, High Density, Teflon Tape 3/4" x 520" Roll
TT35	White High Density, Teflon Tape 3/4" x 520" Roll



MPT_OC5&OC7



MPT_OCTHREE



O2TT



Non-stock/special order items are not cancellable or returnable

Shop online at www.raymurray.com or call 800-628-5044