CO2 Pumps

TURBINE PUMPS (CORO-FLO®)

HIGH DIFFERENTIAL PRESSURE TURBINE MODELS DLF-SERIES Note: DL models connect to motor frame sizes 182TC through 215TC. F-SERIES (FRAME MOUNTED)

DIRECT MOUNT (C)

| Base Model Number | Inlet | Outlet | Ship weight, pump (lbs) |
|-------------------|-----------------|-------------|-------------------------|
| DLF075 | 1–1/2" ASME (a) | 1" ASME (a) | 75 |
| DLF150 | 1-1/2" ASME (a) | 1" ASME (a) | 75 |

Note : (a) Class 300 RF flange

FRAME MOUNT

| Base Model Number | Inlet | Outlet | Ship weight, pump (lbs) |
|-------------------|------------|--------|-------------------------|
| F10 | 1-1/4" NPT | 1" NPT | 48 |
| F12 | 1-1/2" NPT | 1" NPT | 48 |
| F13 | 1-1/2" NPT | 1" NPT | 48 |
| F14 | 1-1/2" NPT | 1" NPT | 48 |



DLF150



BLACKMER LIQUEFIED GAS PUMPS

Blackmer Liquefied Gas Pumps specifically designed for liquid CO2 service. High efficiency sliding vane, positive displacement pumps offer the best combined characteristics of sustained high level performance, energy efficiency, trouble free operation and low maintenance cost.

| RMI Pa | ırt No. | Inlet/Outlet | НР | Capacity GPM | RMI Part No. | Inlet/Outlet | Capacity GPM |
|-------------|-----------|--------------|----|------------------|--------------|----------------|--------------|
| Pump & base | Pump only | inier/Outlet | nr | 50# I 90# | Pump & base | inier/Outlet | 50# I 90# |
| CRLR1.25-DM | CRLR1.25 | 1-1/4″ | 2 | 6 GPM X | TCRLF4 | 4″ 300# flange | 275 245 |
| CRL1.25-DM | CRL1.25 | 1-1/4″ | 3 | 11 GPM 7.5 GPM | | Twin 2" NPT | 275 1 245 |
| CRL1.5-DM | CRL1.5 | 1-1/2″ | 3 | 17 GPM I 15 GPM | | | |

| RMI Pa | rt No. | Inlet/Outlet | Capacity GPM |
|-------------|-----------|--------------|--------------|
| Pump & base | Pump only | inier/Outlet | 50# I 90# |
| CRL2-DM | CRL2 | 2″ | 62 55 |
| CRL3-DM | CRL3 | 3″ | 120 I 95 |
| CRL4-DM | CRL4 | 4" - 3" | 275 245 |

| CRLF4 | 4″ 300# flange Twin 2″ NPT | 275 24 | 5 |
|-------|-------------------------------|----------|---|
| | | | |

CRL-3

BLACKMER BYPASS VALVES

Blackmer Bypass Valves are designed to protect pumps and system components from excessive pressure damage. In operation, Blackmer valves provide exceptional close pressure control, even under widely varying bypass conditions.

| RMI Part No. | Size | Pump Size | STD PSI Range |
|--------------|--------|---------------|------------------|
| BV-3/4 | 3/4″ | 1-1/4 - 1-1/2 | 70-100 |
| BV-1 | 1″ | 1-1/4 - 1-1/2 | 70-100 |
| BV-1-1/4 | 1-1/2" | 1-1/2 - 2″ | 70-100 |
| BV-1-1/2 | 3/4″ | 2 - 3″ | 90-125 |
| BV-2 | 3/4″ | 3 - 4" | 90-125 |

CORKEN BYPASS VALVE

CRL-1.25

Dual purpose automatic priming and differential bypass valve. Allows vapor to return to tank keeping line primed.

| RMI Part No. | Description | Cap. (GPM) |
|--------------|--------------------------------|---------------|
| B166-75 | 3/4" Bypass Valve 50-150 PSI | 30 |
| B166-1 | 1″ Bypass Valve 50–150 PSI | 40 |
| T166-1.25 | 1–1/4" Bypass Valve 50–150 PSI | 80 |
| T166-1.5 | 1–1/2" Bypass Valve 50–150 PSI | 100 |

B166-1

Non-stock/special order items are not cancellable or returnable Shop online at www.raymurray.com or call 800-628-5044