



MR. HEATER BY ENERCO TANK TOP HEATERS

- Made of durable materials and quality construction
- Polished chrome reflector
- Economical- costs pennies per hour to operate

- Automatic safety shut-off
- CSA Certified (MH15T & MH30T only)
- 1-year limited warranty

Fuel Type	RMI Part Number	Capacity BTU/HR	Tank Size	Ignition Type	Description
LP	MH15	8-15,000	1#	manual	single basic
LP	MH15C	8-15,000	1# or 20#	manual	heater / cooker
LP	MH15T	8-15,000	5-20#	manual	single tank mount
LP	MH15TS	8-15,000	5-20#	piezo	single tank mount w/ piezo
LP	MH30T	8-30,000	20#	manual	double tank mount
LP	MH30TS	8-30,000	20#	piezo	double tank mount w/piezo
LP	MH45T	8-45,000	20-100#	manual	triple tank mount



RE-VERBER-RAY TANK TOP HEATERS

- Rugged ceramic burner
- UL Listed hose, regulator and excess flow fitting included
- Adjustable mounting bracket
- Patented safety tip-over device
- CSA design certified safety control and thermocouple
- 90 day limited warranty

Fuel Type	RMI Part Number	Capacity BTU/HR	Tank Size	Ignition Type	Description
LP	P-16T	16,000	20#	manual	basic compact burner
LP	P-32T	32,000	20#	manual	basic full size burner



MR. HEATER PORTABLE CABINET HEATER

- Four easy-roll caster wheels
- Heavy duty steel cabinet-20# cylinder rests securely inside
- Tip over safety shut-off safety switch
- Hose and regulator included
- Low oxygen safety shut-off system (ODS)
- Hi-Med-Low Heat settings
- CSA Certified
- 1-year limited warranty

Fuel Type	RMI Part Number	Capacity BTU/HR	Tank Size	Ignition Type	Description
LP	MH18CH	6-18,000	20#	piezo	radiant portable heater



MR. HEATER BIG BUDDY® HEATER

- Dual ceramic burner tiles with shock absorbing insulation
- Heavy-duty safety wire guard
- Swivel regulator mount makes cylinder installation easy
- Easy carry handle with built-in blower fan
- Low-oxygen safety shut-off (ODS)
- Tip over safety shut-off
- Multi-position heat settings (Lo-Med-Hi)
- CSA Certified
- 1-year limited warranty

Fuel Type	RMI Part Number	Capacity BTU/HR	Tank Size	Ignition Type	Description
LP	MH18B	18,000	(1or2) 1# (1or2) 20#	piezo	dual heat system combines radiant heat with convection heat air flow

*smaller sizes available 4,000 & 9,000 - different designs



© Ray Murray Inc. Edition 11

Tel: 800-628-5044

RAY MURRAY, INC.
Order online at www.raymurray.com
or call for personal assistance

Fax: 800-243-8341

L.B. WHITE PREMIER DUCTABLE UNIT HEATERS

- Rugged construction with tri-shield coating provides protection against abrasion and corrosion
- High volume of air output for maximum heat distribution with versatile indoor placement for heat or air circulation or ducted in from outdoors
- Remote start weather-proof thermostat with 20ft cord and built-in “GO” or “NO GO” diagnostic system
- Dual Fuel units include dual fuel regulator and can be easily switched from one fuel to the other by the turn of a valve handle
- 15ft. hose and regulator included
- 2-year warranty



99.97% Fuel Efficiency

Fuel Type	RMI Part Number	Capacity BTU/HR	Electrical Supply	Ignition Type	Air Output (CFM)	CSA Certified
LP	PREMIER 80	80,000	115/60/1	Direct Spark	450	yes
NG	PREMIER 80N	80,000	115/60/1	Direct Spark	450	yes
LP	PREMIER 170	170,000	115/60/1	Direct Spark	1,200	yes
NG	PREMIER 170N	170,000	115/60/1	Direct Spark	1,200	yes
LP/NG	PREMIER 170 DF	170,000	115/60/1	Direct Spark	1,200	yes
LP	PREMIER 350	350,000	115/60/1	Direct Spark	2,500	yes
NG	PREMIER 350N	350,000	115/60/1	Direct Spark	2,500	yes
LP/NG	PREMIER 350 DF	350,000	115/60/1	Direct Spark	2,500	yes

RMI Part Number	Premier® Air Distribution Equipment
26347	Distribution ducting, white, 12 in. X 12 ft., Premier 80 & 170
22696	Distribution ducting, white, 12 in. X 16.5 ft., Premier 80 & 170
26346	Distribution ducting, gray, 12 in. X 12 ft., Premier 80 & 170
26348	Distribution ducting, plastic, light duty, 12 in. X 12 ft., Premier 80 & 170
22835	Distribution ducting, white, 18 in. X 12 ft., Premier 350
24442	Distribution ducting, plastic, light duty, 18 in. X 12 ft., Premier 350
08979	Duct adapter, Premier 80 & 170
23050	Duct adapter, Premier 350
26350	End diffuser, small, Premier 80 & 170
23189	End diffuser, large, Premier 350

RMI Part Number	Premier® Parts
09454	Thermostat, NEMA 4X with 20 ft. cord - Premier 80 & 170
22920	Thermostat, 2 stage, NEMA 4X with 20 ft. cord - Premier 350
08990	Regulator Premier 80
09911	Regulator Premier 170
09795	Regulator Premier 80N, 170N
25108	Regulator Premier 350, 350N
24600	Gas hose ½" X 15 ft universal with adapters (Premier 80, 80N, 170, 170N)
23078	Gas hose ¾" X 15 ft female quick coupling (Premier 350& 350N)

L.B. WHITE THERMA GROW™ GREENHOUSE HEATERS

- Lower fuel costs, greater efficiency
 - 99+% Fuel conversion efficiency
 - 20% better fuel efficiency than traditional heaters
- Superior heat management
 - Quick response on demand heat
 - Powerful long reaching blower fan
 - Two-stage temperature control (PLUS models)
 - Heating and air circulation models (PLUS models)
- Indoor or outdoor Installation
 - Cabinet design offers multiple indoor location options
 - Easy to install outdoor mounting kit saves growing space
- Trouble-free performance backed by a 10 year warranty
 - Fully enclosed electronic controls, gas valve and motor
 - Safety features include a fully enclosed flame, built-in temperature protection and air flow safety devices
 - Heat treated corrosion resistant components
 - Galvanized steel cabinet (THERMAGROW) and white steel case w/ tri-shield coating (THERMAGROW PLUS)
 - 1-year product warranty and 10-year warrant against heat chamber and case corrosion



Fuel Type	RMI Part Number	Capacity BTU/HR	Electrical Supply	Ignition Type	Air Output (CFM)
LP	THERMA GROW 120	120,000	115/60/1	Hot Surface	1,100
LP	THERMA GROW 120 PLUS	65,000 & 120,000	115/60/1	Hot Surface	1,100
NG	THERMA GROW 120N	120,000	115/60/1	Hot Surface	1,100
NG	THERMA GROW 120N PLUS	65,000 & 120,000	115/60/1	Hot Surface	1,100
LP	THERMA GROW 220	220,000	115/60/1 or 230/60/1	Hot Surface	1,750
LP	THERMA GROW 220 PLUS	120,000 & 220,000	115/60/1 or 230/60/1	Hot Surface	1,750
NG	THERMA GROW 220N	220,000	115/60/1 or 230/60/1	Hot Surface	1,750
NG	THERMA GROW 220N PLUS	120,000 & 220,000	115/60/1 or 230/60/1	Hot Surface	1,750

RMI Part Number	Therma Grow™ Greenhouse Complete Installation and Ventilation Kits
25995	Indoor kit for Therma Grow 120 include: motorized inlet shutter, shuttered exhaust fan, air inlet transition kit, air inlet hood, eyebolts and chains
25985	Indoor kit for Therma Grow 220 include: motorized inlet shutter, shuttered exhaust fan, air inlet transition kit, air inlet hood, eyebolts and chains
24690	Outdoor kit for Therma Grow 120 include: Exhaust shutter and outdoor mount kit
24688	Outdoor kit for Therma Grow 220 include: Exhaust shutter and outdoor mount kit

RMI Part Number	Therma Grow™ Greenhouse Accessories
23651	Indoor mount kit, Therma Grow 120
23652	Indoor mount kit, Therma Grow 220
08748	Eyebolts and chains for indoor mount
23578	Outdoor mount kit, Therma Grow 120
23579	Outdoor mount kit, Therma Grow 220
09381*	Thermostat kit, NEMA 4X single stage
23778*	Thermostat kit, NEMA 4X 2-stage for PLUS models
06553*	Regulator, LP
24414*	Regulator, NG
20714*	Gas hose, ½" X 10 ft. with adapters
08752*	Piping hardware

*required for installation, refer to installation manual

RMI Part Number	Therma Grow™ Greenhouse Ventilation Kits
24742	Exhaust fan with shutter, indoor mount, Therma Grow 120
24741	Exhaust fan with shutter, indoor mount, Therma Grow 220
25994	Inlet shutter with motor, indoor mount, Therma Grow 120
25984	Inlet shutter with motor, indoor mount, Therma Grow 220
23689	Exhaust shutter, outdoor mount, Therma Grow 120
23864	Exhaust shutter, outdoor mount, Therma Grow 220

© Ray Murray Inc. Edition 11

Tel: 800-628-5044

RAY MURRAY, INC.
 Order online at www.raymurray.com
 or call for personal assistance

Fax: 800-243-8341

L.B. WHITE GUARDIAN™ HSI FORCED AIR HEATERS

- Bottom air draw design
- Advanced Service Saver™ with easy-to-see display for monitoring heater's performance
- Indoor or outdoor installations
- Air proving switch and totally enclosed motor for safe, dependable operation
- Galvanized steel cabinet
- Highly efficient direct-fire design
- 115v / 60 cycle / single phase (GUARDIAN 60,100,250)
- 220v / 60 cycle /single phase (GUARDIAN 325)
- 1-Year warranty
- CSA Certified



Fuel Type	RMI Part Number	Capacity BTU/HR	Air Output (CFM)	Fuel Usage	Eye Bolt & Chain	Air Diverter 2 pc Snap-in	Outdoor Mntg. Kit	NEMA 4X T-Stat
LP	GUARDIAN 60	30-60,000	411	2.8 lbs/hr	08748	20111	09810	09454
NG	GUARDIAN 60N	30-60,000	411	60 cu.ft./hr	08748	20111	09810	09454
LP	GUARDIAN 100	50-100,000	686	4.6 lbs/hr	08748	23127	09811	09454
NG	GUARDIAN 100N	50-100,000	686	100 cu.ft./hr	08748	23127	09811	09454
LP	GUARDIAN 250*	160-250,000	1885	11.6 lbs/hr	08748	20048	24097	09454
NG	GUARDIAN 250N*	160-250,000	1885	250 cu.ft./hr	08748	20048	24097	09454
LP	GUARDIAN 325	200-325,000	1700	15.1 lbs/hr	08748	09177	24098	09454
NG	GUARDIAN 325N	200-325,000	1700	325 cu.ft./hr	08748	09177	24098	09454

*can also be set up using a "t" duct diverter pn#25678

L.B. WHITE CLASSIC™ PILOT IGNITION FORCED AIR HEATERS

- Side air draw design
- Fully protected gas valve
- Indoor installations only
- Internal gas pressure trap
- Steel cabinet with tri-shield coating
- 115v / 60 cycle / single phase
- 1-Year warranty



Fuel Type	RMI Part Number	Capacity BTU/HR	Air Output (CFM)	Fuel Usage	Eye Bolt & Chain	Air Diverter 2 pc Snap-in	Air Diverter 1pc Spot weld	NEMA 4X T-Stat
LP	CLASSIC 60	60,000	250	2.8 lbs/hr	standard	07742	00810	09454
NG	CLASSIC 60N	60,000	250	60 cu.ft./hr	standard	07742	00810	09454
LP	CLASSIC 115	115,000	480	5.3 lbs/hr	standard	07434	00808	09454
NG	CLASSIC 115N	115,000	480	115 cu.ft./hr	standard	07434	00808	09454
LP	CLASSIC 170	170,000	700	7.9 lbs/hr	standard	07434	00808	09454
NG	CLASSIC 170N	170,000	700	170 cu.ft./hr	standard	07434	00808	09454